



Poland Petroleum Refinery Sludge Lagoon Demonstration Project

by

D. J. Altman

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

R. L. Brigmon

G. Plaza

Institute for Ecology of Industrial Areas
Poland

A. J. Tien

A. Worsztynowicz

Institute for Ecology of Industrial Areas
Poland

T. C. Hazen

K. Ulfig

Institute for Ecology of Industrial Areas
Poland

A document prepared for 100TH AMERICAN SOCIETY OF MICROBIOLOGY GENERAL MEETING at Los Angeles, CA, USA from 5/21/2000 - 5/25/2000.

DOE Contract No. DE-AC09-96SR18500

This paper was prepared in connection with work done under the above contract number with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

**Available for sale to the public, in paper, from: U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161,
phone: (800) 553-6847,
fax: (703) 605-6900
email: orders@ntis.fedworld.gov
online ordering: <http://www.ntis.gov/ordering.htm>**

**Available electronically at <http://www.doe.gov/bridge>
Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from:
U.S. Department of Energy, Office of Scientific and Technical Information, P.O. Box 62,
Oak Ridge, TN 37831-0062,
phone: (865)576-8401,
fax: (865)576-5728
email: reports@adonis.osti.gov**

Q70

POLAND PETROLEUM REFINERY SLUDGE LAGOON DEMONSTRATION PROJECT


A.J. Tien¹, A.Worsztynowicz², D.J. Altman¹, T.C. Hazen^{1S}, K. Ulfig², G.Plaza², T. Manko²

¹Environmental Biotechnology Section, Westinghouse Savannah River Co. LLC, Aiken SC 29808


²Institute for Ecology of Industrial Areas, 40-833 Katowice, Poland

ABSTRACT

The US Department of Energy and the Institute for Ecology of Industrial Areas have been working together to develop mutually beneficial, cost-effective environmental remediation technologies such as the demonstration of bioremediation techniques for the clean up of acidic petroleum sludge impacted soils at an oil refinery in southern Poland. After an expedited site characterization, treatability study, and a risk assessment study, a remediation strategy was devised. The waste material was composed primarily of high molecular weight paraffinic and polynuclear aromatic hydrocarbons. A biopile design which employed a combination of passive and active aeration in conjunction with nutrient and surfactant application was used to increase the biodegradation of the contaminants of concern.



BIOPILE DESIGN



Site characterization and treatability studies, including soil column and microcosm experiments were conducted prior to selection and design of biopile technology.

SITE DESCRIPTION

Waste from 80 yrs of petroleum processing at the Czechowice Oil Refinery using sulfuric acid extraction process.


Approximately 120 thousand tons of weathered acidic petroleum sludges exist. Ten thousand tons added per year.

Sludge lagoons impacted a total of 3.8 hectares .

Benzo(a)pyrene and BTEX compounds were identified as the primary contributors to risk for present and future site workers.

Approximately 3,300 m³ of contaminated soil (mean TPH concentration of 30,000 ppm) was remediated.

Biopile constructed within the the smallest sludge lagoon (0.8 ha).



Proximity of sludge lagoons to a city park


¹ Present Address: Holderbank Management and Consulting, Corporate Industrial Ecology -ETPS, CH-5113 Holderbank, Switzerland
²Present Address: Lawrence Berkeley National Laboratory, Berkeley, CA

UNCLASSIFIED
 DOES NOT CONTAIN
 UNCLASSIFIED CONTROLLED
 NUCLEAR INFORMATION


ADC & Reviewing Official: *D. Moore Sheldon*
 (Name and Title)
 Date: *5/2/00*

OPERATIONAL CAMPAIGNS (OC)

- OC-1. Mobilization and air injection startup (9/25/97-1/27/98)
- OC-2. Air injection (2/1/98-4/15/98)
- OC-3. Air injection + fertilizer (4/16/98-6/30/98)
- OC-4. Air injection + fertilizer + leachate recirculation (7/1/98-9/29/98)
- OC-5. Air injection + fertilizer + leachate recirculation + surfactant (7/4/99-9/29/99)



Active aeration via air injection



Passive aeration via barometric pumping using BaroBalls™


RESULTS

Over the 20 month project, more than 81% (120 metric tons) of petroleum hydrocarbons were biodegraded. Despite the fact the material treated was highly weathered and very acidic, biodegradation rates of up to 121 mg/kg soil/day in the actively aerated side (82 mg/kg soil/day in the passive side) were achieved in this biopile. Microbial counts and dehydrogenase measurements support the biodegradation rates.

Campaign	Average	Passive	Active
OC-1	80	44	119
OC-2	88	82	94
OC-3	<33	33	0
OC-4	<37	0	37
OC-5	91	60	121

All values in mg/kg soil/day

Baseline (Tons)	OC1	OC2	OC3	OC4	OC5
148	100	68.6	68.6	66.8	28.1
% Remaining	68	46	46	45	19



CONCLUSIONS


- Measurement of dehydrogenase activity (TTC) provides real-time account of biodegradation process.
- Surfactant use can enhance contaminant bioavailability and nutrient utilization, thus increasing contaminant biodegradation.
- Passive aeration useful in areas where utilities are not available and/or when there are no time constraints.
- Passive aeration applicable to facilitated natural attenuation.
- Biopile technology is cost-effective.

REFERENCES

Altman, D. J., Hazen, T. C., A. Tien, A. Worsztynowicz and K. Ulfing. 1997. Czechowice Oil Refinery Bioremediation Demonstration Test Plan. WSRC-MS-97-214. Westinghouse Savannah River Company, Aiken, SC DOE-NITS.





Tien, A. J., A. Worsztynowicz, K. Zacharz, D. Altman, and T. C. Hazen. 1999. Technology Development and Transfer for Environmental Remediation, Sigma Xi Forum on International Cooperation in Science and Technology. Vancouver, B. C. Sigma Xi Press p.191-197.

IETU, 1999. Comprehensive report of remediation applications at an oil refinery in southern Poland, Report prepared for U.S. DOE, FETC.



Site of former sludge lagoon

(A,B,C,D) MPN Petroleum Degraders: Active Deep, Passive Deep, Active Shallow, Passive Shallow



~~6-F-31~~